

BioWeb-B3



Fingerprint



RFID Card



Access Control



USB Host



TCP / IP



Web

Web Enabled Attendance & Access Control terminal

Fast Registry Function, Proprietary Access Control Software Provide, Real-Time Log looks up/Download/Export Reports (Web Server & Software), Support Multi-Badge Function Selectable Bypass mode: Registered/Facility Code/All, Easy setup for Anti-Passback function

SPECIFICATIONS :

Verification Mode
Fingerprint/Card/Password

Fingerprint Capacity
9,590

Display
2.8 inch inch blue background with black characters

Resolution
500dpi

Sensing Area
16 x19mm

1:1 Verification time
<600msec

1:1,000 Identification time
<760msec

Card Capacity
20,000

Communications Method
TCP/IP, Wiegand/RS485

Inbuilt Relays
Door Lock/Ring

Option
USB/Voice

System Log
1,536

Entry Log
51,968

Time Set/Time Zone/Group
255/120/255 Sets

Function Key Setting
400 (Auto/Manual)

Anti-Pass Back/Anti Duress
Yes/Yes

Power Consumption
780mA ± 5%

Power Requirement
9V 1A

Operation Temperature
0?~55?

Dimension/Weight
130x145x51.5mm/450g

Push Data Technology
Logs Data Real Time Push

Dimension/Weight
160.2 * 140.2 * 46.7 mm / 501 g